Lori Barlow

From: Sean Messner

Sent: Tuesday, December 20, 2016 11:02 AM

To: Todd Whipple

Cc: 'Greg Figg'; Gabe Gallinger; John Hohman; Eric Guth

Subject: COSV Painted Hills TIA comments

Attachments: COSV TIA comments_pertinent pages.pdf

Good Morning Todd,

Please find attached the COSV comments on the Painted Hills TIA. I don't believe I duplicated any of WSDOT comments, but if I have, please defer to WSDOT comments on WSDOT facilities.

I've spoken to Ben over the phone yesterday and offered to go through the comments page by page. The offer still stands as I think it would be very good to meet in person to go over the comments. The comments are fairly minor in the grand scheme of things but are necessary to complete study for the project that meets the City standards. I do not think the comments will change the recommendations per say, but rather provide the necessary documentation to validate the recommendations within the report. I appreciate the hard work that you have done on this project and have shown in the documentation within the TIA as the recommendations appear to be very sound and have merit.

Ben emailed WSDOT requesting that an addendum letter be provided by WCE to address the WSDOT comments. I believe that the same memorandum can also be utilized to address the City comments.

Please let me know when you would like to meet to discuss further, or if you'd prefer to discuss via phone, please give me a call.

Thank you Todd, Sean

Sean Messner, P.E. Senior Traffic Engineer City of Spokane Valley

11707 E. Sprague, Suite 106 Spokane Valley, WA 99206

Phone: 509.720.5011 Fax: 509.688.0261

Email: smessner@spokanevalley.org

City of Spokane Valley Comments 12/19/16 SM	

RECEIVED CSV Development Engineering

OCT 1 4 2016

Project #______Name_____Submittal #______

For
Painted Hills PRD

Spokane Valley, Washington
September 14, 2016
2013-1166

- 32nd Ave & Bowdish Rd (AM & PM)
- Dishman-Mica Rd & Bowdish Rd (AM & PM)
- Dishman-Mica Rd & Apt. Access (AM & PM) (Proposed)
- Dishman-Mica Rd & Sundown Dr. (AM & PM) (Proposed)
- Dishman-Mica Rd & S. Comm. Access (AM & PM) (Proposed)
- Dishman-Mica Rd & Thorpe Rd (AM & PM)
- Thorpe Rd & Comm. Access (AM & PM) (Proposed)
- 16th Ave & Pines Rd (AM & PM)
- 16th Ave & SR 27 (AM & PM)
- 32nd Ave & Pines Rd (AM & PM)
- Madison Rd & Painted Hills Ave (AM & PM) (Proposed)
- Madison Rd & 41st Ave (AM & PM) (Proposed)
- Madison Rd & 43rd Ave (AM & PM) (Proposed)
- Madison Rd & 44th Ave (AM & PM) (Proposed)
- Madison Rd & Thorpe Rd (AM & PM)
- 32nd Ave & SR 27 (AM & PM)
- 32nd Ave & Evergreen Rd (AM & PM)
- 32nd Ave & Sullivan Rd (AM & PM)
- 8. This traffic impact analysis follows the City of Spokane Valley Standard for Traffic impact analysis which utilizes level of service analysis for the year 2015 (existing) to establish a baseline of performance and identify any existing concerns in the exiting transportation system. Buildout year scenarios (2025) both with and without the project to determine traffic concurrency or to determine if the added trips of the project on the transportation system would reduce the scoped intersections level of service below the standard.
- 9. Per the City of Spokane Valley Street Standards 3.3.4.6 the buildout year +5 analysis scenario was included as the project is expected to take more than 6 years to complete. The buildout year plus 5 years (2030) both with and without the project will ensure that any proposed mitigation would maintain level of service after buildout.
- 10. Per the City of Spokane Valley Street Standards 3.3.4.6 the buildout year +20 analysis scenario of the mitigated intersection was not included as the proposed year 2025 mitigation at an unsignalized intersection (16th Avenue & Pines Road) does not involve the installation or modification to an intersection controlled with a traffic signal or roundabout.
- 11. An Additional analysis of Peak Hours and cut-through traffic per public comment were included in the public involvement section to respond to a concern that the Midilome East residents had. This additional analysis is not a part of traffic concurrency but is a service provided to the public for their information.

See Conclusion comments at end.

Based upon the analysis, ricid observations, assumptions, methodologies and results which are provided in the body of this report, it is concluded that the development of the proposed project

- There are five queue deficiencies identified at three intersections. These deficiencies were identified as the result of the background growth rate and the background projects as identified at scoping. A review of the City of Spokane Valley Transportation improvement projects (TIP), shows that there are no public improvement projects identified to mitigate the discrepancies at the following intersections and movements:
 - o 16th Avenue & State Route 27, EB Thru, WB Thru
 - o 32nd Avenue & Pines Road, EB Thru
 - 32nd Avenue & State Route 27, WB Thru, WB Left Turn

Year 2030, Buildout Plus 5 Years, with project, with background projects

- There is a Level of Service deficiency identified at the intersection of 16th Avenue & Pines Road, as the southbound approach has 133.7 seconds of average delay, for level of service as described in Chapter 3 of the Spokane Valley Street Standards, and the Level of Service Table 4.3 of the City of Spokane Valley Comprehensive Plan.
- The Level of Service deficiency identified at the intersection of 16th Avenue & Pines Road, originally caused by the background trips and worsened by this project, can be brought back to an acceptable level of service signalizing the intersection and pairing the signal timing with the signal at the intersection of 16th Avenue & State Route 27
- There are five future queue deficiencies at three intersections with two of those intersections operating at acceptable levels of service. These deficiencies were the result of the background growth rate and the background projects as identified within this study and are only incrementally worsened or kept the same by this project. A review of the City of Spokane Valley Transportation improvement projects (TIP), shows that there are no public improvement projects identified to mitigate the discrepancies at the following intersections and movements:
 - o 16th Avenue & State Route 27, EB Thru, WB Thru
 - o 32nd Avenue & Pines Road, EB Thru
 - 32nd Avenue & State Route 27, WB Thru, WB Left Turn

Recommendations

the following;

See Recommendations comments Based upon the concleat end of document.

ject is recommended to provide

- frontage improvements to Dishman-Mica Road, Thorpe Road, and Madison Road per the City of Spokane Valley development process
- A two-way-left-turn-lane north of the Chester Creek Bridge to the property boundary with appropriate taper.
- Bicycle and pedestrian facilities per the City of Spokane Valley Bicycle and Pedestrian Master Plan along the site frontage.
- a northbound right turn lane be considered at the intersection of 32nd Avenue & Pines Road. Coordination with the City of Spokane Valley and the Central Valley School District will be required.
- We also recommend that when warranted by the development conditions that the project contribute its participating percentage in a project to signalize the intersection of 16th Avenue & Pines Road.

FUTURE YEAR TRAFFIC IMPACT ANALYSIS

Future Year Traffic Impact Analysis

Level of service calculations for the buildout Year (2025) & the buildout year plus 5 years (2030) conditions assumed that the existing traffic volumes as shown on Figures 3 & 4 experience an increase above the year 2015 volumes at the established background rate. Two scenarios were examined for the year 2025 (buildout) analysis, as well as the 2030 buildout year plus 5 years. The first scenario assumes that the development has not moved forward and analyzes the scoped intersections with the background growth rate and the background project trips. The second scenario assumes that the development has moved forward to completion and is builtout. The scenario analyzes the scoped intersections with the background growth rate, the background projects, and the project trips. These scenarios will allow a determination to be made of what the future conditions may be with and without the project.

Year 2025 Buildout without the Project, with the Background Projects

The "Paired Signalized Intersections" also includes capacity additions, kground projects has shown in the Synchro model. This needs to be mentioned in the sbody of the report so that it's clear what the proposed improvement Othat is being analyzed is. As a side note, this is one very viable option for improvement. Other options may be considered through the implementation process.

Table 17 - Year 2025 Levels of Service, without the Project, with the Background Projects

INTERSECTION		The state of the s	ak Hour		k Hour
(S)ign (U)nsign		Delay (sec)	LOS	Delay (sec)	LOS
32 nd Ave & University Rd	S	12.2	В	11.9	В
Dishman-Mica Rd & University/Schafer Rd	S	16.4	В	17.2	В
32 nd Ave & Bowdish Rd	S	15.2	В	13.5	В
Dishman-Mica Rd & Bowdish Rd	S	12.8	В	11.8	В
Dishman-Mica Rd & Thorpe Rd	U	11.3	В	10.9	В
16 th Ave & Pines Rd	U	26.2	D	66.4	F
 Paired Signalized Intersections 	(S)	(30.5)	(C)	(23.7)	(C)
16 th Ave & SR 27	S	33.6	С	30.3	C
 Paired Signafized Intersections 		(42.3)	(D) /	(23.4)	(C)
32 nd Ave & Pines Rd	S	27.0	C/	21.9	Ĉ
Madison Rd & Thorpe Rd	U	12.1	B	9.9	A
32 nd Ave & SR 27	S	22.3	12	28.2	С
32 nd Ave & Evergreen Rd	U	11.2 /	В	23.6	С
32 nd Ave & Sullivan Rd	U	12.0	В	13.2	В

The signal phasing for the proposed improvements is not correct. Please refer to WSDOT for comments on the improvement signal phasing, which may adjust

g traffic, as

fic from the

& 11 for the

are shown in the

Table 18 - Year 2025 PM Peak W-O the Project, Intersection Queue Lengths 95th Percentile

INTERSECTION			EB			WB			NB			SB	
(A)vailable Lane Stora (Q)ueue within the Storage La		L	T	R	L	T	R	L	T	R	L	T	R
32 nd Ave & University Rd	Α		345			582		100	400		100	265	
32 Ave & Oliversity Ru	Q		127			98		29	30		88	38	a .
Dishman-Mica Rd &	A	150	1,213	1,213	60	1,978		130	280		90	550	550
University/Schafer Rd	Q	32	291	49	56	80		89	64		53	109	0
32 nd Ave & Bowdish Rd	A	200	590		200	990			445			280	
32 Ave & Bowdish Ku	Q	10	403		37	190			111			135	
Dishman-Mica Rd & Bowdish Rd	A	100	863		100	680			360			290	135
Disimian-wica Kd & Bowdish Kd	Q	18	187		30	96			106			96	0
Dishman-Mica Rd & Thorpe Rd	A					1,303						700	
Dishinan-wica Rd & Thorpe Rd	Q					12.5						5	
16th Ave & Pines Rd*	A				60				662			300	
TO AVE & TIMES RU	Q				5				117.5			265	
16 th Ave & SR 27*	A		60	60		170		240	3,708		325	630	
TO AVE ESK ZV	Q		586	27		310		60	209		150	234	
32 nd Ave & Pines Rd*	Α	240	490		240	980		130	425		160	700	
32 Ave & Thies Ru	Q	26	562		49	327		42	83		48	108	
Madison Rd & Thorpe Rd	Α		1,303						400				
Wadison Ru & Thorpe Ru	Q		10						2.5				
32 nd Ave & SR 27*	Α	170	900		150	165		200	460		265	1,240	
32 Ave & Six 27	Q	136	276		246	470		190	137		97	187	
32 nd Ave & Evergreen Ro	Α	100									75	315	
22 The Carter From Italy	Q	25									30	70	
32 nd Ave & Sullivan Rd	A		600										
	Q		55										
A = Available Space (ft) Q = 95th Rer	enti	le Queue	Length							App	arent De	ficiency	7

^{*}A graphical exhibit of these Queue lengths are shown on Figures 13A through 13c.

Do these queues reflect the proposed improvements or existing conditions? If proposed improvements, show the queue length for the existing conditions, as was performed for the LOS in Table 17. If this table shows existing conditions, show what the queue would be with the proposed improvements. Please note that any traffic signal timing changes will impact the queue storage reported.

Year 2025 with the Project, with the Background Projects

This scenario assumes that the development has moved forward to completion and the background projects have been completed. The traffic volumes for this condition include the traffic volumes, as shown on Figures 10 & 11, plus the project trips as shown on Figures 7 & 8.

Please see Fig The "Paired Signalized Intersections" also includes capacity additions, of service rest as shown in the Synchro model. This needs to be mentioned in the

Table 19 - Ye body of the report so that it's clear what the proposed improvement that is being analyzed is. As a side note, this is one very viable option for improvement. Other options may be considered through the

in inprovement. Other options may be considered through the								
implementation process. (U)nsignanzed (sec) (sec)								
	_	(sec)		(sec)				
32 nd Ave & University Rd	S	12.4	В	12.4	В			
Dishman-Mica Rd & University/Schafer Rd	13	16.9	В	18.3	В			
32 nd Ave & Bowdish Rd	/S	15.6	В	14.7	В			
Dishman-Mica Rd & Bowdish Rd	S	15.7	В	13.3	В			
Dishman-Mica Rd & Apt. Access	U	13.2	В	10.4	В			
Dishman-Mica Rd & Sundown Drive	U	12.6	В	10.8	В			
Dishman- Mica Rd & S. Compa. Access	U	11.5	В	11.3	В			
Dishman-Mica Rd & Thorpe Rd	U	11.9	В	11.9	В			
Thorpe Rd & Comm. Access	U	9.0	A	9.1	A			
16 th Ave & Pines Rd	U	27.3	D	99.2	F			
 Paired Signalized Intersections 	(S)	(31.1)	(C)	(34.8)	(C)			
16 th Ave & SR 27	S	35.9	D	31.3	C			
 Paired Signalized Intersections 		(44.6)	(D)	(28.6)	(C)			
32 nd Ave & Pines Rd	S	32.3	С	26.0	C			
NB Right Turn		(27.6)	(C)	(24.7)	(C)			
Madison Rd & Painted Hills Ave.	U	11.1	В	10.8	В			
Madison Rd & 41 st Ave.	U	10.7	В	10.5	В			
Madison Rd & 43 rd Ave.	U	10.5	В	10.2	В			
Madison Rd & 44 th Ave.	U	9.7	A	9.6	A			
Madison Rd & Thorpe Rd	U	12.4	В	10.4	В			
32 nd Ave & SR 27	S	23.2	С	29.8	С			
32 nd Ave & Evergreen Rd	U	11.6	В	26.1	D			
32 nd Ave & Sullivan Rd	U	12.3	В	13.5	В			

Intersection Level of Service - Deficiency Evaluation

With the project there continues to be a deficiency identified for intersection level of service as described in Chapter 3 of the Spokane Valley Street Standards, and the Level of Service Table 4.3 of the City of Spokane Valley Comprehensive Plan, at the intersection of 16th Avenue & Pines Road. The deficiency in LOS can be remedied by signalizing the intersection and pairing the signal timing with 16th Avenue & Highway 27. We therefore recommend that the project contribute its proportionate share to the signal. The cost of the signal is anticipated at \$475,000 - \$500,000. the proportionate share should be included in the conditions of approval.

Table 20 (continued)

INTERSECTION (A)vailable Lane Storage			EB		WB			NB			SB		
(Q)ueue within the Storage La	ine	L	T	R	L	T Note th	R nat th	ne	T	R	L	T	R
Dishman-Mica Rd & S Comm.					1	ueue							
10 0 0 00mm.	Q					xcee			le				
Dishman-Mica Rd & Thorpe Rd	A					apaci	ty.					700	
The second secon	Q					20	ĬТ					10	
Thorpe Rd & Comm. Access	A											50	
7	Q										-	2.5	
16th Ave & Pines Rd	A				60				662			300	
	Q				5				272.5			347.5	
16 th Ave & SR 2√*	A		60	60		170		240	3,708		325	630	
	Q		645	27		319		60	213		149	238	
32 nd Ave & Pines Rd*	A	240	490	14.	240	980		130	425	150	160	700	
	Q	28	708		112	358		69	97	6	66	183	
Madison Rd & Painted Hills Ave	A		100	A.				50					
	Q		0					0					
Madison Rd & 41st Ave	A		100					50					
	Q		2.5					0					
Madisor Madisor Madisor Madisor Madisor Madisor Do these queues ref conditions? If propose existing conditions, a shows existing cond proposed improvement	sed as v itio	impr was p ns, sł	ovemoerforn ow w	ents, s ned fo hat the	show r the e que	the qu LOS i ue wo	ieue n Ta ould l	lengt ble 1 ⁻ be wi	th for t 7. If th th the		e		
changes will impact	the	que	ie sto	rage re	eport	ed.			9			_	
32 nd Ave & SR 27*	A	170	900		150	165		200	460		265	1,240	- V - ALBOY
	Q	137	281		238	497		199	140		95	194	
32 nd Ave & Evergreen Rd	A	100									75	315	
	Q	27.5									35	82.5	
32 nd Ave & Sullivan Rd	A		600										
	Q		57.5										
A = Available Space (ft) Q = 95th Pen	centi	le Queue	Length							Appa	arent De	ficiency	

^{*}A graphical exhibit of these Queue lengths are shown on Figures 13A through 13c.

There are \underline{no} new deficiencies identified with the proposed project, only the extension of known deficiencies.

Left Turn Analysis at Proposed Project Accesses on Dishman-Mica Road, Thorpe Road & Madison Road along Project Frontage


Per the request of the City of Spokane Valley we have analyzed the proposed accesses to

access allowed to Dishman Mica

Only 1 commercial turn is warranted based upon the WSDOT design manual Exhibit 1310-7a. hmarized here and the exhibits are shown in the appendix:

Table 41 - Lett Turn Analysi	is at Proposed P	roject Accesses.
------------------------------	------------------	------------------

Table 41 - Left Turn Ana	lysis at Proposed Project
Intersection:	Results
Dishman-Mica Road &	NA – no left turns
Apt. Access	allowed (RI-RO)
Dishman-Mica Road &	Plots above the line and
Sundown Drive	warrants left turn lane
Dishman-Mica Road &	Plots below the line
N. Comm. Access	
Dishman-Mica Road &	Plots below the line
S. Comm. Access	
Thorpe Road & Comm.	Plots below the line
Access	
Madison Road & Painted	Plots below the line
Hills Avenue	
Madison Road & 41st	Plots below the line
Avenue	
Madison Road & 43rd	Plots below the line
Avenue	11 40000014-20
Madison Road & 44 th	Plots below the line
Avenue	



As shown in the results only the intersection of Dishman-Mica Road & Sundown Drive meets the threshold to consider a left turn storage lane.

Based upon these results and discussions with the developer regarding the developments frontage improvements, we recommend that on Dishman Mica Road a Two-Way-Left-Turn-Lane (TWLTL) be provided to accommodate the proposed access roads and driveways. The TWLTL is proposed to begin north of the Chester Creek Bridge and end before the extension of the project boundary. Additionally, based upon the City of Spokane Valleys classification of Madison Road as a collector we recommend that that the developer includes the widening of Madison Road for a future TWLTL. These recommendations are incorporated with the analysis of the intersections.

Study Area Intersections Left and Right Turn Warrants

Per the request of the City of Spokane Valley a review of directly impacted left & right turn movements of the study intersections was completed for the Year 2025 with the project in the AM and PM peak hours. The left and right turn movements of each intersection were screened using a rule of thumb consideration to identify potential turn lane needs. The rule of thumb is a movements that exceeded a volume of 300 vehicles for a left turn movement, and 100 vehicles for a right turn movement. This rule of thumb is only used as an indicator, as the decision to install a turn tane is based upon multiple variables including Intersection Level of Service, Signal Tiexceeding 300 vph, and Movement Queue.

warrants dual left-

is at Study Area Intersections

turn lanes (rule of		udy Are				
thumb).	ASSESSMENT OF THE PARTY OF	k Hour		k Hour	Existing Condition	Recommendation
	Ivmt	Trips	Mvmt	Trips		
32 nd Ave. &	WB Rt	132	WB Rt	70	Shared Rt & Thru	None
University Rd.	SB Lt	69	SB Lt	114	Turn Lane	
Dishman-Mica Rd &	WB RT	34	WB Rt	34	50' Full Flare	None
University/Schafer	SB Lt	25	SB Lt	18	Turn Lane	
32 nd Ave & Bowdish	WB Lt	29	WB Lt	103	SB left-turn lane is v	warranted per
	WB Rt	14	WB Rt	58	NCHRP 745 and W	
	NB Lt	63	NB Lt	25	would be included in	n the frontage
	NB Rt	37	NB Rt	89	improvements as pr	
	SB Lt	83	SB Lt	48	No Turn lane	
Dishman-Mica Rd &	WB Lt	42	WB Lt	31	Turn Lane	None
Bowdish	WB Rt	46	WB Rt	43	No turn lane.	
	NB Rt	30	NB Rt	27	Slight Flare	
	SB Lt	32	SB Lt	35	No Turn Lane	
Dishman-Mica Rd &	WB Rt	113	WB Rt	103	Shared Lt & Rt	None
Thorpe Rd	NB Rt	14	NB Rt	18	No Turn Lane	
	SB Lt	55	SB Lt	139	No Turn Lane	
16 th Ave. & Pines Rd	WB Lt	54	WB Lt	81	No Turn Lane	See 2025 W-OProj
- Ah	NB Rt	256	NB Rt	202	Slight Flare	Recommendation
16 th Ave & Hwy 27	EB Lt	237	EB Lt.	194	Shared Lt & Thru	none
32 nd Ave. & Pines	EB Rt	8	EB Rt	71	No turn lane.	See Below
Rd	WB Lt	63	WB Lt	133	Turn Lane	
	NB Lt	63	NB Lt	64	Turn Lane	
	NB Rt	168	NB Rt	83	No Turn lane	
Madison & Thorpe	EB Lt	91	EB Lt	47	No Turn Lane	None
	SB Rt	79	SB Rt	44	No Turn Lane	
32 nd Ave. & State	EB Lt	154	EB Lt	92	Turn Lane	None
Route 27	EB Rt	71	EB Rt	213	Turn Lane	
	NB Lt	145	NB Lt	149	Turn Lane	
	SB Rt	82	SB Rt	77	50' Full Flare	
32 nd Ave. &	EB Lt	244	EB Lt	214	Turn Lane	None
Evergreen Rd	SB Rt	115	SB Rt	223	Turn Lane	
32 nd Ave. &	EB Lt	241	EB Lt	294	Shared Lt & Rt	None
Sullivan Rd	SB Rt	177	SB Rt	370	Turn Lane	

The Intersection of 16th Avenue & Pines Road northbound right turn movement meet the rule of thumb in the Year 2025 with the project, however because of the close proximity of intersections, the signal controls the operation of the northbound approach. So the addition of a right turn lane would still operate as before, rendering any improvement as moot.

Year 2030 Buildout plus 5 years without the Project, with the Background Projects

This scenario The "Paired Signalized Intersections" also includes capacity additions, have been corn as shown in the Synchro model. This needs to be mentioned in the the existing tribody of the report so that it's clear what the proposed improvement the traffic from that is being analyzed is. As a side note, this is one very viable option 14 & 15 for the for improvement. Other options may be considered through the are shown in implementation process.

Table 22 - Year 2030 Buildout Plus 5, Levels of Service, without the Project

INTERSECTION AM Peak Hour PM Peak Hour								
	// -				k Hour			
(S)igna (U)nsigna	/	Delay (sec)	LOS	Delay (sec)	LOS			
32 nd Ave & University Rd	S	12.4	В	12.2	В			
Dishman-Mica Rd & University/Schafer Rd	S	16.8	В	17.6	В			
32 nd Ave & Bowdish Rd	S	16.5	В	14.7	В			
Dishman-Mica Rd & Bowdish Rd	S	13.4	В	12.1	В			
Dishman-Mica Rd & Thorpe Rd	U	11.6	В	11.2	В			
16th Ave & Pines Rd	U	30.8	D	99.9	F			
 Paired Signalized Intersections 	(S)	(30.8)	(C)	(35.2)	(D)			
16 th Ave & SR 27	S	37.4	D	32.8	C			
 Paired Signalized Intersections 		(46.7)	(D)	(28.7)	(C)			
32 nd Ave & Pines Rd	S	28.8	С	24.6	C			
Madison Rd & Thorpe Rd	U	12.4	В	10.1	В			
32 nd Ave & SR 27	S	23.4	С	30.0	С			
32 nd Ave & Evergreen Rd	U	11.5	В	27.1	D			
32 nd Ave & Sullivan Rd	U	12.3	В	13.9	В			

Intersection Level of Service - Deficiency Evaluation

Without the project there is a deficiency identified for intersection level of service as described in Chapter 3 of the Spokane Valley Street Standards, and the Level of Service Table 4.3 of the City of Spokane Valley Comprehensive Plan, at the intersection of 16th Avenue & Pines Road. The deficiency in LOS can be remedied by signalizing the intersection and pairing the signal timing with 16th Avenue & Highway 27.

Year 2030 Buildout Plus 5 Years with the Project, with the Background Projects

This scenario assumes that the development has moved forward to completion and the

background projec The "Paired Signalized Intersections" also includes capacity additions, this condition incluas shown in the Synchro model. This needs to be mentioned in the shown on Figures body of the report so that it's clear what the proposed improvement scenario. A summathat is being analyzed is. As a side note, this is one very viable option for improvement. Other options may be considered through the

Table 23- Year 20 implementation process.

INTERSECTION INTERSECTION	AM Peak Hour PM Peak Ho				
(S)igna (U)nsigna		Delay (sec)	LOS	Delay (sec)	LOS
32 nd Ave & University Rd	S	12.7	В	12.8	В
Dishman-Mica Rd & University/Schafer Rd	S	17.3	В	18.9	В
32 nd Ave & Bowdish Rd	S	16.9	В	16.0	В
Dishman-Mica Rd & Bowdish Rd	S	16.9	В	14.0	В
Dishman-Mica Rd & Apt. Access	U	13.4	В	10.5	В
Dishman-Mica Rd & Sundown Drive	U	12.9	В	10.9	В
Dishman- Mica Rd & S. Comm Access	U	11.6	В	11.5	В
Dishman-Mica Rd & Thorpe Rd	U	12.2	В	12.2	В
Thorpe Rd & Comm. Access	U	9.1	A	9.1	A
16 th Ave & Pines Rd	U	32.3	D	141.2	F
 Paired Signalized Intersections 	(S)	(31.4)	(C)	(36.7)	(D)
16 th Ave & SR 27	S	40.7	D	34.3	C
 Paired Signalized Intersections 		(49.3)	(D)	(29.0)	(C)
32 nd Ave & Pines Rd	S	34.9	С	26.9	C
 NB Right Turn lane 		29.2	(C)	27.1	(C)
Madison Rd & Painted Hills Ave.	U	11.2	В	10.9	В
Madison Rd & 41st Ave.	U	10.8	В	10.6	В
Madison Rd & 43 rd Ave.	U	10.6	В	10.2	В
Madison Rd & 44 th Ave.	U	9.7	A	9.8	A
Madison Rd & Thorpe Rd	U	12.8	В	10.6	В
32 nd Ave & SR 27	S	24.3	С	31.9	С
32 nd Ave & Evergreen Rd	U	11.8	В	30.3	D
32 nd Ave & Sullivan Rd	U	12.6	В	14.2	В

Intersection Level of Service - Deficiency Evaluation

With the project there continues to be a deficiency identified for intersection level of service as described in Chapter 3 of the Spokane Valley Street Standards, and the Level of Service Table 4.3 of the City of Spokane Valley Comprehensive Plan, at the intersection of 16th Avenue & Pines Road. The deficiency in LOS can be remedied by signalizing the intersection and pairing the signal timing with 16th Avenue & Highway 27.

The report reflects build-out in phases, and per the Street Standards 3.3.4.6 requires analysis of the build-out year + 5 years. The LOS for the build-out + 5 years was provided and meets the standards. However, the queue analysis was not provided for review and therefore does not meet the street standards. Please provide the build-out $\sqrt[3]{+}$ 5 years queue analysis per the street standards for review. The conclusions already identify the results of the 2030 analysis, provide the analysis to confirm the conclusions.

CONCLUSIONS & RECOMMENDATIONS

Conclusions

Based upon the analysis, field observations, assumptions, methodologies and results which are provided in the body of this report, it is concluded that the development of the proposed project will generate new trips on the existing transportation system and that those trips while affecting level of service will generally not degrade LOS below concurrency levels, except at the intersection of 16th Avenue & Pines Road. Additionally, the queue deficiencies identified, carry through the scenarios from the existing condition to the future conditions, and the project only adds to an already existing condition. This conclusion was reached and has been documented within the body of this report.

Existing Condition

Chapter 3 of the Spokane Valley Street Stand; appears the proposed improvement the City of Spokane Valley Comprehensive P project resolves this queue issue, but

There are four queue deficiencies identified at need clarification in the tables to acceptable levels of service, there is no public reflect this. these discrepancies.

Based on Tables 18 & 20, the project adds queues to 16th & Pines that There are no Level of Service deficiencies ide block SR 27 traffic. See Figure 13A. It

- o 16th Avenue & State Route 27, EB Thru, WB Thru
- o 32nd Avenue & State Route 27, WB left, WB Thru

Left Turn lanes on Dishman Mica Road, Thorpe Road, and Madison Road

- The intersection of Dishman-Mica Road & Sundown Drive warrants a southbound left turn lane
- Based upon the results and discussions with the developer Dishman-Mica Road & Madison are proposed to include a TWLTL for the project accesses.

Study Area Intersections Left and Right Turn Warrants

and SB Thorpe

The Intersection of 16th Avenue & Pines Road northbound right turn movement meet the rule of thumb in the Year 2025 With the project, however because of the close proximity of intersections, the signal controls the operation of the northbound approach. So the addition of a right turn lane would still operate as before, rendering any improvement as moot.

The intersection of 32nd Avenue & Pines Road northbound right turn movement meets the rule of thumb and the project anticipates adding trips to the movement. Therefore a northbound right turn lane will be considered.

> Appendix comments: The AM Synchro files have the pedestrian data entered correctly as discussed. However, the PM Synchro files did not have the pedestrian data entered as discussed. Inputing the pedestrian data as discussed may impact the delays

Whipple Con at the intersections. Please review/revise accordingly.

Painted Hills PRD

Year 2025, Buildout, without project, with background projects

- There is a Level of Service deficiency identified at the intersection of 16th Avenue & Pines Road, for level of service as described in Chapter 3 of the Spokane Valley Street Standards, and the Level of Service Table 4.3 of the City of Spokane Valley Comprehensive Plan. The deficiency in LOS can be remedied by signalizing the intersection and pairing the signal timing with 16th Avenue & Highway 27.
- There are five queue deficiencies identified at three intersections. These deficiencies were identified as the resulThe "Paired Signalized Intersections" also includes capacity additions, identified at scoping as shown in the Synchro model. This needs to be mentioned in the discrepancies. Please body of the report so that it's clear what the proposed improvement

o 16th Avenue that is being analyzed is. As a side note, this is one very viable option o 32nd Avenue for improvement. Other options may be considered through the

o 32nd Avenue implementation process.

Year 2025, Buildout, with project, with background projects

There is a Level of Service deficiency identified at the intersection of 16th Avenue & Pines Road, for level of service as described in Chapter of the Spokane Valley Street Standards, and the Level of Service Table 4.3 of the City of Spokane Valley

The report reflects build-out in phases, and per the Street Standards 3.3.4.6 requires analysis of the build-out year + 5 years. The LOS for the build-out + 5 years was provided and meets the standards. However, the queue analysis was not provided for review and therefore does not meet the street standards. Please provide the build-out + 5 years queue analysis per the street standards for review. As shown below, the conclusions already identify the results of the 2030 analysis. provide the analysis to confirm the conclusions.

at the intersection of 16th Avenue & Pines trips and worsened by this project, can be ice by signalizing the intersection and pairing way 27.

previously identified at three intersections acceptable levels of service. These and growth rate and the background projects as crementally worsened or kept the same by this oject identified to mitigate these discrepancies. found discrepancies.

Thru, WB Thru

- o 32nd Avenue & Pines Road, EB Thru
- o 32nd Avenue & State Route 27, WB Thru, WB Left Turn

Year 2030, Buildout Plus 5 Years, without project, with background projects

- There is a Level of Service deficiency identified at the intersection of 16th Avenue & Pines Road, for level of service as described in Chapter 3 of the Spokane Valley Street Standards, and the Level of Service Table 4.3 of the City of Spokane Valley Comprehensive Plan. The deficiency in LOS can be remedied by signalizing the intersection and pairing the signal timing with 16th Avenue & Highway 27.
- There are five queue deficiencies identified at three intersections. These deficiencies were identified as the result of the background growth rate and the background projects as identified at scoping. There is no public improvement project identified to mitigate these discrepancies. Please see the analysis for the details of the found discrepancies.

- 16th A The "Paired Signalized Intersections" also includes capacity additions.
- 32nd as shown in the Synchro model. This needs to be mentioned in the
- 32nd Abody of the report so that it's clear what the proposed improvement that is being analyzed is. As a side note, this is one very viable option Year 2030, Buildou for improvement. Other options may be considered through the

implementation process. There is a Level of Service deficiency identified at the intersection of 16th Avenue & Pines Road, for level of service as described in Chapter 3 of the Spokane Valley Street Standards, and the Level of Service Table 4.3 of the City of Spokane Valley

- Comprehensive Plan. The Level of Service deficiency identified at the intersection of 16th Avenue & Pines Road, originally caused by the background trips and worsened by this project, can be brought back to an acceptable level of service by signalizing the intersection and pairing the signal timing with 16th Avenue & Highway 27.
- There are the same five queue deficiencies previously identified at three intersections with two of those intersections operating at acceptable levels of service. These deficiencies were the result of the background growth rate and the background projects as identified within this study and are only incrementally worsened or kept the same by this project. There is no public improvement project identified to mitigate these discrepancies. Please see the analysis for the details of the found discrepancies.
 - o 16th Avenue & State Route 27, EB Thru, WB Thr SB turn lane @
 - o 32nd Avenue & Pines Road, EB Thr

Thorpe/DM

32nd Avenue & State Route 27, WB Thru, WB Left Turn

Recommendations

Based upon the conclusions within this study the proposed project is recommended to provide the following;

- frontage improvements to Dishman-Mica Road, Thorpe Road, and Madison Road per the City of Spokane Valley development process
- A two-way-left-turn-lane north of the Chester Creek Bridge to the property boundary with appropriate taper.
- Bicycle and pedestrian facilities per the City of Spokane Valley Bicycle and Pedestrian Master Plan along the site frontage.
- a northbound right turn lane be considered at the intersection of 32nd Avenue & Pines Road. Coordination with the City of Spokane Valley and the Central Valley School District will be required.
- We also recommend that the development contribute a proportionate share of the cost of the proposed signal at the intersection of 16th Avenue & Pines Road. Agreed. Thank you

The report reflects build-out in phases, and per the Street Standards 3.3.4.6 requires analysis of the build-out year + 5 years. The LOS for the build-out + 5 years was provided and meets the standards. However, the queue analysis was not provided for review and therefore does not meet the street standards. Please provide the build-out + 5 years queue analysis per the street standards for review. As shown below, the conclusions already identify the results of the 2030 analysis. provide the analysis to confirm the conclusions.

Agreed. The proposed improvement identified in this report is a very viable option. and the proportionate share discussion would be a condition of approval.

s PRD

for analyzing

accordingly.

72